

Water-proof IR COLOR DOME CAMERA

KD-320S12I\N\P KD-320A12I\N\P



- More than 420 /350TV Line
- High Sensitivity 0Lux(With IR LED)
- AWB/ AGC
- S/N Ratio More than 48 dB
- Water-proof IP66 standard
- Built-in 12piecesLED/10-15 meter
- Vandal Housing 10 pound



MODEL	KD-320S12I\N	KD-320A12I\N
	KD-320S12I\P	KD-320A12I\P
Image sensor	1/3" COLOR CCD(SONY)	1/3" COLOR CCD(SHARP)
Picture element	NTSC:510(H)*492(V) PAL:500(H)*582(V)	NTSC:512(H)*492(V) PAL:512(H)*582(V)
Horizontal resolution	More than 420 TV Line	More than 350 TV Line
SYNC.System	Internal	
Minimum Illumination	0Lux(With IR LED)	
S/N Ratio (AGC OFF)	More than 48 dB	
Gamma	0.45	
Gain Control	Auto	
LED	Built-in 12piecesLED/15meter	Built-in 12piecesLED/10meter
Water-proof	IP66	
Vandal Housing	10 pound	
White Balance	Auto(2500°K~9500°K)	
Electronic Shutter	Auto:1/60(1/50)~1/100000 Sec	
IR LED Spec	EffectiveDistance:(12pcs)/850nm/16000hrs	
Video Output	1.0Vp-p 75 ohm	
Power Supply	DC12V	
Power Consumption	350mA	320mA
Lens Type	3.6mm/F2.0 Board Lens	
Operating Temperature	-10°C~+50°C	
Dimensions	109mm(D)×75mm(H)	
Weight	405g	
Lens Option	6.0mm/8.0mm/12mm F2.0	

