

DS-2CC502/572P-M**Key Features**

- Compact Structure Design
- HIKVISION CCD(improved 1/3 inch SONY CCD)
- Day / Night with Auto Switch
- Low illumination: 0.1Lux @ F1.2
- Auto White Balance, Auto Gain Control, Electronic Shutter Control and Backlight Compensation
- Digital Signal Processing
- Internal Synchronization
- Advanced Engineering Design, High Reliability

Application

Your Best Choice of cost-efficient solutions for Hotels, Supermarkets, Offices, Corridors, Stairs and etc. (For indoor installation)

Specification

Model Parameter	DS-2CC502P-M	DS-2CC572P-M
Image Sensor	HIKVISION CCD(improved 1/3"SONY Super HAD CCD)	
Signal System	PAL	
Effective Pixels	500 (H) × 582 (V)	752 (H) × 582 (V)
Min. Illumination	0.1Lux @ F1.2	
Electronic Shutter	1/50s to 1/100,000s	
Lens	3.6mm @ F2.0	
Horizontal Resolution	420TVL	540TVL
Synchronization	Internal Synchronization	
Video Output	1Vp-p Composite Output (75Ω / BNC)	
S/N Ratio	More than 48 dB	
BLC	ON	
Working Temperature	-10°C~60°C	
Power Supply	DC12V ±10%	
Power Consumption	2W MAX	
Dimension (mm)	Φ110 × 62 (Φ4.36" × 2.46")	
Weight	330g (0.72lbs)	

Dimension

